











Timber width (inches)		2"	4"	6"	8"	10"	12"
60 A 60 S	 2"-4" 3 1/2" - 11"		min. 2" x 3 1/2" / max. 4" x 11" (2") 2 3/8" x 3 1/8" max. 4" 330 - 990 lbs				
80 A 80 S	 3 1/8" - 5 1/2" 3 1/2" - 11"			min. 3 1/8" x 3 1/2" / max. 5 1/2" x 11" 3 1/8" x 4 3/4" max. 5 1/2" 590 - 1610 lbs			
100 A 100 S	 4" - 6 1/4" 3 1/2" - 11"			min. 4" x 3 1/2" / max. 6 1/4" x 11" 4" x 5 1/2" max. 6 1/4" 810 - 2050 lbs			
120 A 120 S	 4 3/4" - 7 1/16" 3 1/2" - 11"  4 3/4" - 7 7/8" 3 1/2" - 13"			N°120A : min. 4 3/4" x 3 1/2" / max. 7 1/16" x 11" N°120S : min. 4 3/8" x 3 1/2" / max. 7 7/8" x 13" 4 3/4" x 6 1/4" max. 7 1/16" (7 7/8") 1020 - 2645 lbs			
160+ A	 5 1/2" - 11 13/16" 3 1/2" - 16 1/2"				min. 5 1/2" x 3 1/2" / max. 11 13/16" x 16 1/2" 5 1/2" 6 1/4" x 11 13/16" 1255 - 3745 lbs		

ARUNDA



Min. / max. section  
(width x height)



Optimal timber widths



Min. / max. feasible  
timber widths



Min. / max. working loads (lbs)  
depending on dimensions